



AUTOMATIC TRANSMISSION FLUID

Setting Harris	PHOLE THE FULL ST MULTINE HEALT AND AND AND AND AND AND AND AND AND AND	to Fill SIT Millitude so Con US AIT * 55-5 260 AU IS AIT	Pione Part # 910 Part # 910	Pi0110 Dart # 970 111 323 333	118 F 23 F 11 F
GM DEXRON®-II	0.9, 1], 5	969, 11 , 55	10 m 11 m	30p × 40	200 41x
(1973 - 1993)					
GM DEXRON [®] -III (1993 - 2005)	1	1	1		
GM DEXRON®-VI (2005 - PRESENT)		1			
FORD M2C-33F/M2C-33G TYPE F (1967 - 1987 EST.)					<
Ford Mercon [®] (1987 - 2004)	1		1		
Ford Mercon [®] V (1995 - 2004)			1		
Ford Mercon [®] LV (2007 - Current)		1			
Chrysler +3 (up to 2006)					
Chrysler +4 (2002 - Current)				1	
Honda TF-Z1		1	1		
Nissan Matic-J		1			
Toyota T-IV		1	1		
Toyota WS		1			

This chart is a general application guide. Always consult your owners manual for the recommended fluid for your specific application.



AUTOMATIC TRANSMISSION FLUID



Automatic Transimission Fluid For Vehicles Requiring MERCON®/DEXRON-III®

Pronto Automatic Transmission Fluid is specially formulated using only the finest lubricating oils and a technologically advanced additive system. This high quality product is suitable for use where DEXRON®-II, DEXRON®-III or MERCON® fluids are specified. Engineered to extend transmission life and smooth operation, Pronto Automatic Transmission Fluid provides the following benefits:

- Excellent high and low temperature protection
- Stable friction properties for smooth and consistent shifting •
- Excellent shear stability •
- · Outstanding resistance to wear, oxidation and varnish deposits

Do not use this product in General Motors vehicles after model year 2005 and Ford vehicles after model year 2006. Do not use this product in transmissions that specify Ford Type F, MERCON® V, MERCON® SP fluids or GM DEXRON®-VI fluid. Warranty valid only in the U.S.

ATF+4[®] Automatic Transmission Fluid

Pronto ATF+4® Automatic Transmission Fluid is a uniquely blended, quality engineered fluid designed to meet the specific requirements of Chrysler and FCA automatic transmissions/transaxles and certain Hvundai and Mitsubishi transmissions. This high-quality product is formulated for use where MS-9602®, MS-7176®, ATF+®, ATF+2® ATF+3® or ATF+4® fluids are specified. ATF+4® is a trademark of FCA US LLC, used under license. Pronto ATF+4® Automatic Transmission Fluid provides:

- · Excellent protection against wear and shudder resistance
- Resistance to thickening due to high temperatures •

Friction stability to maintain smooth consistent shift performance Warranty valid only in the U.S.

Full Synthetic Multi-Vehicle Low Viscosity Automatic Transimission Fluid Dexron®-VI and Mercon® LV Approved

Pronto Full Synthetic DEXRON®-VI Automatic Transmission Fluid is specially formulated with synthetic base stocks and advanced additive technology. This high-quality product meets the requirements of General Motors automatic transmissions calling for DEXRON®-VI fluid. This fluid is also suitable for use where DEXRON®-II, DEXRON®-III, JASO M315(1A), Toyota WS, or Toyota T-IV fluids are recommended. Suitable for use in Ford vehicles that require Low Viscosity ATF (excluding Type F). Not for use in CVT applications.

- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures
- · Friction stability to maintain smooth consistent shift performance

Warranty valid only in the U.S.

Full Synthetic Multi-Vehicle Automatic Transmission Fluid

Pronto Multi-Vehicle ATF is specially formulated with a unique combination of synthetic base stocks and an advanced additive technology to ensure peak performance of almost any automatic transmission. This premium-quality product meets and exceeds the frictional and wear requirements of most automatic transmissions manufactured after 1983 including many foreign vehicles. Pronto Multi-Vehicle ATF is recommended for a wide range of vehicles requiring DEXRON®-III/MERCON® or MERCON® V fluids including: GM(pre-2006 models), Ford (all models except where Type F is required), Mazda (all models), Honda/Acura (all models except Continuous Variable Transmissions [CVTs]), Subaru (all models), Volkswagen (pre-2006models). Additionally recommended for transmissions calling for Toyota Type T, T-III, T-IV; Nissan Matic-D, Matic-J, Matic-K; LT71141; Diamond SP-II and SP-III, ATF 3403-M; Honda Z1 (except CVT). Benefits include:

- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures

Friction stability to maintain smooth consistent shift performance Warranty valid only in the U.S.

Type F Automatic Transmission Fluid

Pronto Type F Automatic Transmission Fluid is specially formulated using only high quality lubricating oils and a technologically advanced additive system.

- · Excellent high and low temperature protection
- Stable friction properties for smooth and consistent shifting
- Excellent shear stability

Engineered to extend transmission life and smooth operation of Ford automatic transmissions not requiring MERCON® or DEXRON® type fluid. Type F fluid is approved for all Ford automatic transmissions built prior to 1977 and certain models for years 1977 through 1980. Meets Ford specification for high static friction fluid and all warranty requirements for transmissions recommending a Type F fluid. Warranty valid only in the U.S.